



CF2

Calcite Filter

Domestic Manual

Aqua Co.
FILTERS

Est. 1987

Product Description: Calcite is a food grade safe to drink pH adjustment mineral readily absorbed via flow of water through the material. Calcite filters are used to raise pH in acidic waters to a neutral level, typically pH 7.0 is optimum. Low pH waters are very corrosive and outside of safe water guidelines.

Specifications

Type	Calcite pH Correction Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	13" (33cm) x 54" (137cm) wound fibreglass pressure vessel	
Media	80kg of calcite	
Control Valve	Clack flow through valve	
Flow Rate	Continuous	30 litres per minute
	Peak	40 litres per minute
Pressure	Maximum	600 kpa (85 psi)
	Minimum	175 kpa (25 psi)
Pipe Sizes	Inlet/outlet	3/4" (20mm)
	Drain	N/A

Note: Product specifications are a guide only and can change without notice.

Water Filters Pty Ltd

Unit 3, 100 Frobisher St, Osborne Park WA 6017

Telephone: 08 6156 0220

Email: sales@waterfilter.com.au

www.waterfilter.com.au

www.wawaterfilters.com.au

Aqua Co.
FILTERS

To us it's more than just water...